

# BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
2 December 2004 (02.12.2004)


PCT

(10) International Publication Number  
**WO 2004/103228 A1**

- (51) International Patent Classification<sup>7</sup>: **A61F 2/46, A61B 17/17**
- (21) International Application Number:  
PCT/US2004/011335
- (22) International Filing Date: 12 April 2004 (12.04.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
10/438,295 14 May 2003 (14.05.2003) US
- (71) Applicant (for all designated States except US): **ARCHUS ORTHOPEDICS, INC.** [US/US]; 8624 - 154th Avenue NE, Redmond, Washington 98052 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **REILEY, Mark** [US/US]; 360 Magnolia Avenue, Piedmont, California 94611 (US). **YUAN, Hansen** [US/US]; 5066 Pine Valley Drive, Fayetteville, New York 13066 (US). **STINSON, David** [US/US]; 15009 NE 195th Street, Woodinville, Washington 98072 (US). **JONES, Lawrence** [US/US]; 11701 Baca Road, Conifer, Colorado 80433 (US).
- (74) Agents: **SHAY, James et al.; WILSON SONSINI GOODRICH & ROSATI**, 650 Page Mill Road, Palo Alto, California 94304-1050 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PROSTHESES AND TOOLS FOR REPLACEMENT OF NATURAL FACET JOINTS WITH ARTIFICIAL FACET JOINT SURFACES



(57) Abstract: Tools for installing artificial cephalad and caudal vertebral facet joint prostheses are provided. Specifically, an installation fixture for aligning and installing caudal, cephalad, or caudal and cephalad facet joint prostheses is provided. Also provided is a guide tool for use with the installation fixture for guiding the affixation of a prosthesis to a vertebra.

WO 2004/103228 A1

BEST AVAILABLE COPY



**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**PROSTHESES AND TOOLS FOR  
REPLACEMENT OF NATURAL FACET JOINTS WITH  
ARTIFICIAL FACET JOINT SURFACES**

**FIELD OF THE INVENTION**

5           This invention relates to prostheses for treating various types of spinal pathologies, as well as to methods of treating spinal pathologies.

**BACKGROUND OF THE INVENTION**

**I. VERTEBRAL ANATOMY**

10           As Fig. 1 shows, the human spinal column 10 is comprised of a series of thirty-three stacked vertebrae 12 divided into five regions. The cervical region includes seven vertebrae 12, known as C1-C7. The thoracic region includes twelve vertebrae 12, known as T1-T12. The lumbar region contains five vertebrae 12, known as L1-L5. The sacral region is  
15 comprised of five vertebrae 12, known as S1-S5. The coccygeal region contains four vertebrae 12, known as Co1-Co4.

          Fig. 2 shows a normal human lumbar vertebra 12. Although the lumbar vertebrae 12 vary somewhat according to location, they share many features common to most vertebrae 12. Each vertebra 12 includes a  
20 vertebral body 14 and posterior elements as follows:

          Two short bones, the pedicles 16, extend backward from each side of the vertebral body 14 to form a vertebral arch 18. At the posterior end of each pedicle 16 the vertebral arch 18 flares out into broad plates of bone known as the laminae 20. The laminae 20 fuse with each other to form  
25 a spinous process 22. The spinous process 22 serves for muscle and ligamentous attachment. A smooth transition from the pedicles 16 into the laminae 20 is interrupted by the formation of a series of processes.

          Two transverse processes 24 thrust out laterally on each side from the junction of the pedicle 16 with the lamina 20. The transverse  
30 processes 24 serve as levers for the attachment of muscles to the vertebrae 12. Four articular processes, two superior 26 and two inferior 28, also rise from the junctions of the pedicles 16 and the laminae 20. The superior articular processes 26 are sharp oval plates of bone rising upward on each side from the union of the pedicle 16 with the lamina 20.  
35 The inferior processes 28 are oval plates of bone that extend in an inferior direction on each side.

          The superior and inferior articular processes 26 and 28 each have a natural bony structure known as a facet. The superior articular facet 30 faces upward or superiorly, while the inferior articular facet 31 faces

downward. As Fig. 3 shows, when adjacent (i.e., cephalad and caudal) vertebrae 12 are aligned, the facets 30 and 31, capped with a smooth articular cartilage, interlock to form a facet joint 32, also known as a zygapophysial joint.

5       The facet joint 32 is composed of a superior half and an inferior half. The superior half is formed by the vertebral level below the joint 32, and the inferior half is formed by the vertebral level above the joint 32. For example, in the L4-L5 facet joint, the superior portion of the joint is formed by bony structure on the L-5 vertebra (e.g., a  
10       superior articular surface and supporting bone on the L-5 vertebra), and the inferior portion of the joint is formed by bony structure on the L-4 vertebra (e.g., an inferior articular surface and supporting bone on the L-4 vertebra).

As also shown in Fig. 3, an intervertebral disc 34 between each pair  
15       of vertebrae 12 permits relative movement between vertebrae 12. Thus, the structure and alignment of the vertebrae 12 permit a range of movement of the vertebrae 12 relative to each other.

## II. FACET JOINT DYSFUNCTION

Back pain, particularly in the "small of the back", or lumbosacral  
20       (L4-S1) region, is a common ailment. In many cases, the pain severely limits a person's functional ability and quality of life. Such pain can result from a variety of spinal pathologies.

Through disease or injury, the laminae, spinous process, articular  
processes, or facets of one or more vertebrae can become damaged, such  
25       that the vertebrae no longer articulate or properly align with each other. This can result in an undesired anatomy, pain or discomfort, and loss of mobility.

For example, the vertebral facet joints can be damaged by either  
traumatic injury or by various disease processes. These disease processes  
30       include osteoarthritis, ankylosing spondylolysis, and degenerative spondylolisthesis. The damage to the facet joints often results in pressure on nerves, also called a "pinched" nerve, or nerve compression or impingement. The result is pain, misaligned anatomy, and a corresponding loss of mobility. Pressure on nerves can also occur without  
35       facet joint pathology, e.g., a herniated disc.

One type of conventional treatment of facet joint pathology is  
spinal stabilization, also known as intervertebral stabilization.  
Intervertebral stabilization prevents relative motion between the  
vertebrae. By preventing movement, pain can be reduced. Stabilization can  
40       be accomplished by various methods.

One method of stabilization is posterior spinal fusion. Another method of stabilization is anterior spinal fusion, fixation of any number of vertebrae to stabilize and prevent movement of the vertebrae.

Another type of conventional treatment is decompressive laminectomy. This procedure involves excision of the laminae to relieve compression of nerves.

These traditional treatments are subject to a variety of limitations and varying success rates. Furthermore, none of the described treatments puts the spine in proper alignment or return the spine to a desired anatomy. In addition, stabilization techniques, by holding the vertebrae in a fixed position, permanently limit the relative motion of the vertebrae, altering spine biomechanics.

#### SUMMARY OF THE INVENTION

There is a need for prostheses, installation tools, and methods that overcome the problems and disadvantages associated with current strategies and designs in various treatments for spine pathologies.

The invention provides prostheses, installation tools, and methods designed to replace natural facet joints at virtually all spinal levels including L1-L2, L2-L3, L3-L4, L4-L5, L5-S1, T-11-T12, and T12-L1. The prostheses, installation tools, and methods can restore a desired anatomy to a spine and give back to an individual a desired range of relative vertebral motion. The prostheses, installation tools, and methods also can lessen or alleviate spinal pain by relieving the source of nerve compression or impingement.

For the sake of description, the prostheses that embody features of the invention will be called either "cephalad" or "caudal" with relation to the portion of a given natural facet joint they replace. As previously described, a given natural facet joint has a superior half and an inferior half. In anatomical terms, the superior half of the joint is formed by the vertebral level below the joint (which can thus be called the caudal portion of the facet joint, i.e., because it is near the feet). The inferior half of the joint is formed by the vertebral level above the joint (which can thus be called the cephalad portion of the facet joint, i.e., because it is near the head). Thus, a prosthesis that, in use, replaces the caudal portion of a facet joint (i.e., the superior half) will be called a "caudal" prosthesis. Likewise, a prosthesis that, in use, replaces the cephalad portion of a facet joint (i.e., the inferior half) will be called a "cephalad" prosthesis.

One aspect of the invention provides an installation tool for implanting a prosthesis assembly. According to this aspect of the

invention, the tool includes right and left caudal facet joint bearing element attachment mechanisms; and a caudal facet joint bearing element spacing adjuster (such as an actuator) adapted to change the spacing between right and left caudal facet joint bearing element attachment mechanisms. The tool may include caudal and cephalad facet joint bearing element alignment elements adapted and configured to mate with corresponding alignment elements on facet joint bearing elements. The installation tool may also include right and left cephalad facet joint bearing element attachment mechanisms oriented with the right and left caudal facet joint bearing element attachment mechanisms such that a right cephalad facet joint bearing element mounted in the right cephalad facet joint bearing element attachment mechanism aligns with a right caudal facet joint bearing element mounted in the right caudal facet joint bearing element attachment mechanism and a left cephalad facet joint bearing element mounted in the left facet joint bearing element attachment mechanism aligns with a left caudal facet joint bearing element mounted in the left caudal facet joint bearing element attachment mechanism. The installation tool may also include an insertion path guide interface adapted and configured to orient a fixation element insertion path guide in a specific orientation with respect to at least one of the right and left cephalad facet joint bearing surfaces. The insertion path guide interface may also be adapted and configured to orient a fixation element insertion path guide to guide the attachment of a cephalad facet joint bearing element to a vertebra without blocking access to a pedicle portion of the vertebra.

Another aspect of the invention provides a tool for installing a facet joint prosthesis. According to this aspect of the invention, the tool includes a caudal facet joint bearing surface attachment mechanism; a cephalad facet joint bearing surface attachment mechanism adapted and configured to align a cephalad joint bearing surface with a caudal facet joint bearing surface mounted in the caudal facet joint bearing surface attachment mechanism; and an insertion path guide interface. The insertion path guide interface may be adapted and configured to orient a fixation element insertion path guide in a specific orientation with respect to a cephalad facet joint bearing surface. The insertion path guide interface may also be adapted and configured to orient a fixation element insertion path guide to guide the orientation of a cephalad facet joint fixation element in a lamina portion of a vertebra. The insertion path guide interface may also be adapted and configured to orient a fixation element insertion path guide to guide the attachment of a

cephalad facet joint bearing element to a vertebra without blocking access to a pedicle portion of the vertebra. The caudal facet joint bearing surface attachment mechanism and the cephalad facet joint bearing surface attachment mechanism may also be further adapted and configured to place the caudal facet joint bearing surface and the cephalad facet joint bearing surface in compression.

Another aspect of the invention provides a guide tool for guiding the insertion path of a fixation element for a cephalad facet joint bearing element of a facet joint prosthesis. According to this aspect of the invention, the guide tool includes a handle; a facet joint bearing element alignment interface; and an insertion path guide surface. The guide tool may include an arm extending from the handle and being adapted and configured to orient the insertion path guide surface along an axis extending through a lamina portion of a vertebra.

Another aspect of the invention is a method for implanting a cephalad facet joint prosthesis to replace a removed cephalad portion of a natural facet joint on a vertebra. This method includes the steps of placing the cephalad facet joint prosthesis in a desired position with respect to the vertebra; aligning a guide tool with the cephalad facet joint prosthesis; and using the guide tool to guide an insertion path for a cephalad facet joint fixation element. In the method, the placing step may include placing the cephalad facet joint prosthesis between a caudal facet joint bearing surface and the vertebra, and the aligning step may include aligning a guide tool alignment interface with cephalad facet joint prosthesis. The method may also include the step of forming a passage in the vertebra, such as by drilling, and the using step may include the step of inserting the cephalad facet joint fixation element, such as through a lamina portion of the vertebra.

Yet another aspect of the invention provides a facet joint prosthesis installation assembly. According to this aspect of the invention, the installation assembly includes a caudal facet joint bearing surface attachment mechanism; a cephalad facet joint bearing surface attachment mechanism adapted and configured to align a cephalad joint bearing surface with a caudal facet joint bearing surface mounted in the caudal facet joint bearing surface attachment mechanism; a guide tool for guiding the insertion path of a fixation element for a cephalad facet joint bearing surface of the facet joint prosthesis; and a guide tool interface adapted and configured to orient the guide tool to guide the insertion path of a cephalad facet joint bearing surface fixation element in a vertebra.

Other features and advantages of the inventions are set forth in the following Description and Drawings, as well as in the appended Claims.

#### DESCRIPTION OF THE DRAWINGS

Figure 1 is a lateral elevation view of a normal human spinal  
5 column;

Figure 2 is a superior view of a normal human lumbar vertebra;

Figure 3 is a lateral elevation view of a vertebral lumbar facet  
joint;

Figure 4 is a posterior view of an artificial facet joint prosthesis  
10 installed in a patient according to one embodiment of this invention;

Figure 5 is a left side view of the embodiment of Figure 4, as  
installed in a patient;

Figure 6 is yet another view of the embodiment of Figure 4, as  
installed in a patient;

15 Figure 7A is a cross-sectional view of a cephalad bearing element  
and fixation element according to the embodiment of Figure 4;

Figure 7B is a posterior view of a pair of artificial cephalad and  
caudal facet joint prostheses according to one embodiment of this  
invention;

20 Figure 7C is a top view of a pair of artificial cephalad and caudal  
facet joint prostheses in the embodiment of Figure 7A;

Figure 7D is a left view of a pair of artificial cephalad and caudal  
facet joint prostheses in the embodiment of Figure 7A;

Figure 7E is a bottom view of a pair of artificial cephalad and  
25 caudal facet joint prostheses in the embodiment of Figure 7A;

Figure 7F is an anterior view of a pair of artificial cephalad and  
caudal facet joint prostheses in the embodiment of Figure 7A;

Figure 8A is a perspective view of an installation fixture according  
to one embodiment of this invention;

30 Figure 8B is a top view of the installation fixture of Figure 8A;

Figure 8C is a side view of the installation fixture of Figure 8A;

Figure 8D is a back view of the installation fixture of Figure 8A;

Figure 9 is an exploded view of the installation fixture of Figure 8  
along with a pair of caudal facet bearing elements and a pair of cephalad  
35 facet bearing elements according to one embodiment of the invention;

Figures 10A-D are views of a guide tool according to one embodiment  
of the invention;

Figure 11 is a posterior view of the installation fixture of Figures  
8 and 9 to which a pair of caudal facet bearing elements and a pair of  
40 cephalad bearing elements have been attached and with the caudal bearing



elements attached to the patient;

Figure 12 is a left side view of the installation fixture and bearing elements of Figure 11 with the caudal bearing elements attached to the patient;

5        Figure 13 is a perspective view of the installation fixture and bearing elements of Figures 11 and 12 showing a guide tool according to one embodiment of this invention;

Figure 14 is a perspective view of the installation fixture and bearing elements of Figures 11 and 12 showing the use of a drill bit with  
10       the guide tool according to one embodiment of this invention.

The invention may be embodied in several forms without departing from its spirit or essential characteristics. The scope of the invention is defined in the appended claims, rather than in the specific description preceding them. All embodiments that fall within the meaning  
15       and range of equivalency of the claims are therefore intended to be embraced by the claims.

#### DETAILED DESCRIPTION

Although the disclosure hereof is detailed and exact to enable those skilled in the art to practice the invention, the physical embodiments  
20       herein disclosed merely exemplify the invention that may be embodied in other specific structure. While the preferred embodiment has been described, the details may be changed without departing from the invention, which is defined by the claims.

Figures 4-7 show artificial cephalad and caudal facet joint  
25       prostheses 36 and 50 for replacing a natural facet joint according to one aspect of this invention. Cephalad prosthesis 36 has a bearing element 38 with a bearing surface 40. In this embodiment, bearing surface 40 has a convex shape. Bearing element 38 may be formed from biocompatible metals (such as cobalt chromium steel, surgical steels, titanium, titanium  
30       alloys, tantalum, tantalum alloys, aluminum, etc.), ceramics, polyethylene, biocompatible polymers, and other materials known in the prosthetic arts, and bearing surface 40 may be formed from biocompatible metals (such as cobalt chromium steel, surgical steels, titanium, titanium alloys, tantalum, tantalum alloys, aluminum, etc.), ceramics,  
35       polyethylene, biocompatible polymers, and other materials known in the prosthetic arts.

Depending on the patient's disease state, the condition of the patient's natural facet joint—including the facet joint's strength, location and orientation—may not be acceptable. As shown in Figures 4-7,  
40       therefore, the natural cephalad and caudal facet joint surfaces have been

removed to enable the installation of a prosthetic facet joint without limitations presented by remaining portions of the natural facet joint.

In one embodiment of the invention, fixation element 42 attaches cephalad prosthesis 36 to a vertebra 60 in an orientation and position that places bearing surface 40 in approximately the same location as the natural facet joint surface the prosthesis replaces. The prosthesis may also be placed in a location other than the natural facet joint location without departing from the invention, such as by orienting the fixation element along a different angle, by moving the joint cephalad or caudad, or by moving the joint medially or laterally.

In the embodiment shown in Figures 4-7, fixation element 42 is a screw. Other possible fixation elements include headless screws, stems, corkscrews, wire, staples, adhesives, bone cements, and other materials known in the prosthetic arts.

In this embodiment of the invention, the cephalad facet joint prosthesis attaches to a posterior element of the vertebra, such as one or portions of the lamina and/or the spinous process. For example, as shown in Figures 4-6, fixation element 42 may extend through a lamina portion 62 of vertebra 60 at the base of spinous process 64, traversing the vertebra midline as defined by the spinous process 64 and through another lamina portion 66. This orientation of the fixation element is similar to that used in translaminal facet joint screw fixation, as known in the art. Other orientations of fixation element 42 are possible, of course, depending on the dictates of the specific vertebral anatomy and the desires of the clinician. For example, fixation element 42 may extend through only one lamina portion, only through the spinous process, etc.

Unlike other facet joint prostheses that attach to the pedicle, this embodiment's use of one or more posterior elements of the vertebra to attach the cephalad facet joint prosthesis of this invention does not block access to the pedicle area, leaving this area free to be used to attach other prostheses or devices. Other embodiments of the invention may block the pedicle area, of course, without departing from the scope or spirit of the invention. In addition, because of the inherent strength of the lamina, the cephalad facet joint prosthesis may be affixed without the use of bone cement, especially when using a bone ingrowth surface or trabecular metal.

In the orientation shown in Figures 4-6 as well as in some alternative embodiments, after insertion the fixation element's proximal end 43 (preferably formed to mate with a suitable insertion tool) and distal end 44 lie on opposite sides of the lamina. Bearing element 38

attaches to the distal end 44 of fixation element 42 to be disposed between a caudal facet joint bearing surface (either natural or artificial, such as the artificial caudal facet joint prosthesis described below) and a portion of the vertebra, such as the lamina portion shown in Figures 4-6. To attach bearing element 38 to fixation element 42 in the embodiment shown in Figure 4, a hole 46 in bearing element 38 is formed with a Morse taper that mates with the distal end 44 of fixation element 42. Other means of attaching bearing element 38 to fixation element 42 may be used, of course, such as other Morse or other taper connections, machine screw threads, NPT screw threads or other known mechanical fastening means. Fixation element 42 may be coated with antimicrobial, antithrombotic, hydroxyapatite, or osteoinductive materials to promote bone ingrowth and fixation. Bearing element 38 may be attached to fixation element 42 before or after implantation in the patient, depending on the manner of implantation and the requirements of the situation.

Prosthesis 36 may be used to form the cephalad portion of a facet joint with either a natural caudal facet joint portion or an artificial caudal facet joint prosthesis.

Figures 4-7 also show an artificial caudal joint prosthesis 50 for replacing the superior half of a natural facet joint according to one aspect of this invention. Caudal prosthesis 50 has a bearing element 52 with a bearing surface 54. In this embodiment, bearing surface 54 is concave. Bearing element 52 may be formed from biocompatible metals (such as cobalt chromium steel, surgical steels, titanium, titanium alloys, tantalum, tantalum alloys, aluminum, etc.), ceramics, polyethylene, biocompatible polymers, and other materials known in the prosthetic arts, and bearing surface 54 may be formed from biocompatible metals (such as cobalt chromium steel, surgical steels, titanium, titanium alloys, tantalum, tantalum alloys, aluminum, etc.), ceramics, polyethylene, biocompatible polymers, and other materials known in the prosthetic arts.

In one embodiment, the natural caudal facet surface has been removed, and fixation element 56 attaches prosthesis 50 to a vertebra 70 via a pedicle in an orientation and position that places bearing surface 54 in approximately the same location as the natural facet joint surface the prosthesis replaces. In an alternative embodiment, the bearing surface 54 may be placed in a location different than the natural facet joint surface, either more medial or more lateral, more cephalad or more caudad, and/or rotated from the natural anatomical orientation and orientation. In addition, in other embodiments the caudal component can

be attached to the vertebral body in addition to the pedicle or to the vertebral body alone.

As shown in the embodiment of Figures 4-7, fixation element 56 is a screw attached to bearing element 54 via a hole 58 formed in bearing element 52 and is inserted into a pedicle portion 72 of vertebra 70. Other possible fixation elements include stems, corkscrews, wire, staples, adhesives, bone cements, and other materials known in the prosthetic arts. Fixation element 56 can also be inserted into the vertebral body in addition to or in place of the pedicle.

In this embodiment, bearing element 52 has a serrated fixation surface 57 adapted to contact a contact portion 74 of vertebra 70. This optional fixation surface 57 helps prevent rotation of the bearing element 52. In addition, fixation surface 57 may be coated with bone ingrowth material, and any optional serrations increase the surface area for bone ingrowth. As shown in Figure 5, in this embodiment the entire bearing surface 54 is posterior to surface 57 and contact portion 74.

Prosthesis 50 may be used to form the caudal portion of a facet joint with either a natural cephalad facet joint portion or an artificial cephalad facet joint prosthesis.

Figures 7A-F show the artificial facet joint prosthesis according to one embodiment of this invention apart from the vertebrae. As shown, cephalad bearing surface 40 and caudal bearing surface 54 meet to form an artificial facet joint. As seen best in Figure 7B, the width of caudal bearing surface 54 along its transverse axis is greater than the width of cephalad bearing surface 40 along its transverse axis. This feature helps align the cephalad and caudal joints during implant. In addition, this feature permits the point of contact between the two bearing surface to change with flexion, extension, left and right rotation and lateral bending of the patient's spine.

The prostheses of Figures 4-7 may be implanted without special tools. One embodiment of the invention, however, includes an installation fixture to assist with the implantation procedure. Figures 8-14 show installation tools used to implant two artificial facet joints, i.e., two cephalad facet joint prostheses and two corresponding caudal facet joint prostheses. The invention also includes installation tools for implanting a single facet joint prosthesis, two caudal facet joint prostheses, two cephalad facet joint prostheses, a caudal and cephalad joint prosthesis, or any other combination of facet joint prostheses.

As shown in Figures 8 and 9, installation fixture 80 has alignment elements 82 to align the cephalad bearing elements 38 and caudal bearing

elements 52. In this embodiment, the alignment elements are two dowels for each bearing element. Alignment elements 82 mate with corresponding alignment elements in the bearing elements, such as holes 84 (shown, e.g., in Figure 7B) formed in cephalad bearing elements 38 and caudal bearing elements 52. Other alignment elements may be used, of course, such as pins, grooves, indentations, etc. Attachment elements such as screws 86 attach the bearing elements 38 and 52 to the installation fixture via screw holes 88 (shown, e.g., in Figure 7B) formed in the bearing elements and in installation fixture 80.

When attached to installation fixture 80, cephalad and caudal bearing surfaces 40 and 54 are in contact and in proper alignment with respect to each other, as shown in Figure 8. In one embodiment, the cephalad and caudal bearing surfaces 40 and 54 are preloaded to be in compression when attached to installation fixture 80. To bring the pairs of bearing surfaces in proper alignment with respect to the patient's vertebrae, the spacing between the pairs of bearing surfaces might need to be adjusted. In the embodiment of Figures 8, 9 and 11-14, installation fixture 80 has two bearing support components 90 and 92 that move in a controlled manner with respect to each other. Specifically, in this embodiment a threaded shaft 94 extends between support components 90 and 92. Shaft 94 engages bores formed in support components 90 and 92; one or both of the bores are threaded so that rotation of shaft 94 causes support components 90 and 92 to move towards or away from each other. Shaft 94 may be provided with a thumbwheel 96 or other actuator for ease of use. One or more guide rods 98 may be provided to maintain the alignment of support components 90 and 92. Other means of moving the cephalad/caudal bearing elements pairs with respect to each other may be used, such as a guided or unguided sliding connection between installation fixture elements.

In use, after preparing the implant site by removal of all or a portion of existing natural cephalad and caudal facet joint portions of the cephalad and caudal vertebrae 60 and 70, respectively, of the spine motion segment, bearing elements 38 and 52 are attached to installation fixture 80 as described above. The spacing between the bearing element pairs is then adjusted using thumbwheel 96 to align the fixation holes 58 of caudal bearing elements 52 with the proper fixation screw insertion sites in the pedicle portions of the caudal vertebra (or other suitable location), thus placing the artificial facet joints in positions corresponding to the position of natural facet joints or in any other position desired by the physician, including positions that do not

correspond to the position of natural facet joints. Passages aligning with holes 58 are formed and in the pedicle—or into another part of the caudal vertebra near or adjacent to the pedicle—using a drill, awl, pedicle probe, or other tool known in the surgical arts. Fixation screws 56 are then inserted through holes 58 into the pedicle or other portion of the caudal vertebra to attach the caudal bearing elements as well as the entire prosthesis and installation fixture to the caudal vertebra 70, as shown in Figures 11 and 12. Alternatively, self-tapping screws or other caudal fixation elements may be used, thereby eliminating the need to pre-form the passages.

Thereafter, the cephalad bearing elements are attached to the cephalad vertebra 60. In one embodiment, an insertion path is first determined for each fixation element, then a passage is formed along the insertion path corresponding to cephalad bearing element holes 46 (e.g., in the lamina at the base of the spinous process and through the lamina on the other side, through only one lamina portion, through the spinous process, etc.). Fixation screws 42 can then be inserted through the holes 46 into the passages. Alternatively, self-tapping screws or other caudal fixation elements may be used, thereby eliminating the need to pre-form the passages.

After all four bearing elements have been affixed, the installation fixture 80 may be detached and removed. Installation fixture 80 may be used to implant fewer than four bearing elements, of course.

Figures 10, 13 and 14 show a tool that may be used to define the insertion path (location, orientation, etc.) for the fixation element of the left cephalad bearing element. For example, the tool may be used to guide the formation of a cephalad bearing element attachment passage for the left bearing element. A corresponding mirror image tool may be used for the right cephalad bearing element. In alternative embodiments, a single tool may be used for defining the insertion path for both left and right cephalad bearing elements.

As shown, tool 100 has a handle 102 and an alignment interface (such as dowels 104 in tool 100 and holes 106 in fixture 80) to align the tool in the proper orientation with respect to installation fixture 80 and a cephalad facet joint bearing element. With the caudal and cephalad bearing elements still attached to installation fixture 80 and preferably with caudal bearing elements already affixed to the caudal vertebra 70, tool 100 engages installation fixture through the alignment interface as shown in Figures 13 and 14. In this position, tool 100 may be used to define an insertion path for the cephalad fixation elements.

In the embodiment shown in Figures 10, 13 and 14, the insertion path guide is a drill guide 108 supported by arms 110 and 112 and is aligned with hole 46 in cephalad bearing element 38 by the alignment interface between installation fixture 80 and guide tool 100. In this embodiment, 5 drill guide 108 is a tube, but other guide elements may be used, such as a guide groove or surface. A drill bit 114 may be inserted through drill guide 108 to form an insertion passage, such as a passage through a lamina portion of the cephalad vertebra. A fixation screw may then be inserted through the passage in the cephalad vertebra and into the Morse 10 taper connection of hole 46 (or other type connection, as discussed above) of cephalad bearing element 38. As discussed above, the fixation screw may be coated with a bone ingrowth material. Alternatively, a self-tapping screw may be used, thereby removing the need to pre-form a passage.

15 A mirror image tool may then be used to define an insertion path or to form a hole for the right cephalad bearing element, which is then affixed to the vertebral body in the same way. The installation fixture is then removed, such as by unscrewing screws 86.

As mentioned above, in alternative embodiments the guide tool may be 20 used to define a path for a self-tapping screw or other fixation element that does not require the use of a drill. In those embodiments, element 108 may be used to define a path for the self-tapping screw or other fixation element. The fixation element path may be through only a single lamina portion, through the spinous process alone, or any other suitable 25 path.

In some embodiments, the entire prosthesis other than the bearing surface may be coated with bone ingrowth material.

The above described embodiments of this invention are merely descriptive of its principles and are not to be limited. The scope of 30 this invention instead shall be determined from the scope of the following claims, including their equivalents.

What is claimed is:

1. A tool for installing a facet joint prosthesis, the tool comprising:

5 right and left caudal facet joint bearing element attachment mechanisms; and

a caudal facet joint bearing element spacing adjuster adapted and configured to change the spacing between right and left caudal facet joint bearing element attachment mechanisms.

10 2. The tool of claim 1 wherein the caudal facet joint bearing element spacing adjuster comprises an actuator.

3. The tool of claim 1 further comprising right and left caudal facet joint bearing element alignment elements adapted and configured to mate with corresponding alignment elements on caudal facet joint bearing elements.

15 4. The tool of claim 1 further comprising right and left cephalad facet joint bearing element attachment mechanisms oriented with the right and left caudal facet joint bearing element attachment mechanisms such that a right cephalad facet joint bearing element mounted in the right cephalad facet joint bearing element attachment mechanism  
20 aligns with a right caudal facet joint bearing element mounted in the right caudal facet joint bearing element attachment mechanism and a left cephalad facet joint bearing element mounted in the left facet joint bearing element attachment mechanism aligns with a left caudal facet joint bearing element mounted in the left caudal facet joint bearing  
25 element attachment mechanism.

5. The tool of claim 4 wherein the right and left cephalad facet joint bearing element attachment mechanisms and the right and left caudal facet joint bearing element attachment mechanisms are adapted and configured to orient the right and left cephalad facet joint bearing  
30 elements with the right and left caudal facet joint bearing elements prior to contacting the facet joint prosthesis with a vertebra.

6. The tool of claim 4 wherein the caudal facet joint bearing element spacing adjuster is further adapted and configured to change the spacing of the right and left cephalad facet joint bearing elements.

35 7. The tool of claim 6 wherein the right cephalad facet joint bearing element attachment mechanism is affixed to the right caudal facet joint bearing element attachment mechanism and the left cephalad facet joint bearing element attachment mechanism is affixed to the left caudal facet joint bearing element attachment mechanism.

40 8. The tool of claim 4 further comprising right and left



cephalad facet joint bearing element alignment elements adapted and configured to mate with corresponding alignment elements on cephalad facet joint bearing elements.

5 9. The tool of claim 4 further comprising an insertion path guide interface adapted and configured to orient a fixation element insertion path guide in a specific orientation with respect to at least one of the right and left cephalad facet joint bearing surfaces.

10 10. The tool of claim 4 further comprising an insertion path guide interface adapted and configured to orient a fixation element insertion path guide to guide the orientation of a cephalad facet joint fixation element in a lamina portion of a vertebra.

15 11. The tool of claim 4 further comprising an insertion path guide interface adapted and configured to orient a fixation element insertion path guide to guide the attachment of a cephalad facet joint bearing element to a vertebra without blocking access to a pedicle portion of the vertebra.

20 12. The tool of claim 4 further comprising right and left insertion path guide interfaces each adapted and configured to orient a fixation element insertion path guide in a specific orientation with respect to the right and left cephalad facet joint bearing surfaces, respectively.

25 13. The tool of claim 4 further comprising right and left insertion path guide interfaces each adapted and configured to orient a fixation element insertion path guide to guide the insertion path of a cephalad facet joint fixation element in a lamina portion of a vertebra.

30 14. The tool of claim 4 further comprising right and left insertion path guide interfaces each adapted and configured to orient a fixation element insertion path guide to guide the attachment of a cephalad facet joint bearing element to a vertebra without blocking access to pedicle portions of the vertebra.

15. A tool for installing a facet joint prosthesis, the tool comprising:

35 a caudal facet joint bearing surface attachment mechanism;  
a cephalad facet joint bearing surface attachment mechanism adapted and configured to align a cephalad joint bearing surface with a caudal facet joint bearing surface mounted in the caudal facet joint bearing surface attachment mechanism; and  
an insertion path guide interface.

40 16. The tool of claim 15 wherein the insertion path guide interface is adapted and configured to orient a fixation element

insertion path guide in a specific orientation with respect to a cephalad facet joint bearing surface.

17. The tool of claim 15 wherein the insertion path guide interface is adapted and configured to orient a fixation element  
5 insertion path guide to guide the orientation of a cephalad facet joint fixation element in a lamina portion of a vertebra.

18. The tool of claim 15 wherein the insertion path guide interface is adapted and configured to orient a fixation element  
insertion path guide to guide the attachment of a cephalad facet joint  
10 bearing element to a vertebra without blocking access to a pedicle portion of the vertebra.

19. The tool of claim 15 wherein the caudal facet joint bearing surface attachment mechanism and the cephalad facet joint bearing surface attachment mechanism are further adapted and configured to place the  
15 caudal facet joint bearing surface and the cephalad facet joint bearing surface in compression.

20. A guide tool for guiding the insertion path of a fixation element for a cephalad facet joint bearing element of a facet joint prosthesis, the guide tool comprising:

20 a handle;  
a facet joint bearing element alignment interface; and  
an insertion path guide surface.

21. The guide tool of claim 20 wherein the handle has a handle axis, the guide tool further comprising an arm extending from the handle  
25 and being adapted and configured to orient the insertion path guide surface along an axis other than the handle axis.

22. The guide tool of claim 21 wherein the arm comprises a first section extending perpendicularly from the handle axis and a second section extending from the first section parallel with the handle axis.

30 23. The guide tool of claim 20 wherein the handle has a handle axis, the guide tool further comprising an arm extending from the handle and being adapted and configured to orient the insertion path guide surface along an axis extending through a lamina portion of the vertebra when the handle axis is oriented substantially perpendicular to a central  
35 axis of a vertebra.

24. The guide tool of claim 20 wherein the insertion path guide surface comprises a tube.

25. The guide tool of claim 20 wherein the insertion path guide surface is adapted and configured to accommodate a drill bit.

40 26. The guide tool of claim 20 wherein the facet joint bearing

surface alignment interface comprises protrusions extending from the guide tool.

27. A facet joint prosthesis installation assembly comprising:  
a caudal facet joint bearing surface attachment mechanism;  
5 a cephalad facet joint bearing surface attachment mechanism adapted and configured to align a cephalad joint bearing surface with a caudal facet joint bearing surface mounted in the caudal facet joint bearing surface attachment mechanism;  
a guide tool for guiding the insertion path of a fixation element  
10 for a cephalad facet joint bearing surface of the facet joint prosthesis;  
and

a guide tool interface adapted and configured to orient the guide tool to guide the insertion path of a cephalad facet joint bearing surface fixation element in a vertebra.

15 28. The assembly of claim 27 wherein the guide tool interface is further adapted and configured to orient the guide tool to guide the insertion path of the cephalad facet joint bearing surface fixation element in a lamina portion of the vertebra.

29. The assembly of claim 27 wherein the guide tool interface is  
20 further adapted and configured to orient the guide tool to guide the insertion path of the cephalad facet joint bearing surface fixation element to the vertebra without blocking access to a pedicle portion of the vertebra.

30. The assembly of claim 27 wherein the caudal facet joint  
25 bearing surface attachment mechanism comprises a right caudal facet joint bearing surface attachment mechanism and the cephalad facet joint bearing surface attachment mechanism comprises a right cephalad facet joint bearing surface attachment mechanism, the assembly further comprising a left caudal facet joint bearing surface attachment mechanism and a left  
30 cephalad facet joint bearing surface attachment mechanism adapted and configured to align a cephalad joint bearing surface with a caudal facet joint bearing surface mounted in the left caudal facet joint bearing surface attachment mechanism.

31. The assembly of claim 30 further comprising an actuator  
35 adapted and configured to change the spacing between the right and left caudal facet joint bearing surface attachment mechanisms.

32. The assembly of claim 31 wherein the actuator is further adapted and configured to changed the spacing between the right and left cephalad facet joint bearing surface attachment mechanisms.

40 33. The assembly of claim 30 wherein the guide tool interface is

a first guide tool interface, the assembly further comprising a second guide tool interface adapted and configured to orient the guide tool to guide the insertion path of a cephalad facet joint bearing surface fixation element in the vertebra.

5           34. The assembly of claim 30 wherein the guide tool is a first guide tool and the guide tool interface is a first guide tool interface, the assembly further comprising a second guide tool and a second guide tool interface adapted and configured to orient the second guide tool to guide the insertion path of a cephalad facet joint bearing surface  
10           fixation element in the vertebra.

          35. The assembly of claim 27 wherein the caudal facet joint bearing surface attachment mechanism and the cephalad facet joint bearing surface attachment mechanism are further adapted and configured to place the caudal facet joint bearing surface and the cephalad facet joint  
15           bearing surface in compression.

          36. The assembly of claim 27 wherein the guide tool comprises a handle and an insertion path guide surface.

          37. The assembly of claim 36 wherein the handle has a handle axis, the guide tool further comprising an arm extending from the handle and being adapted and configured to orient the insertion path guide surface along an axis other than the handle axis.  
20           

          38. The assembly of claim 37 wherein the arm comprises a first section extending perpendicularly from the handle axis and a second section extending from the first section parallel with the handle axis.

25           39. The assembly of claim 36 wherein the handle has a handle axis, the guide tool further comprising an arm extending from the handle and being adapted and configured to orient the insertion path guide surface along an axis extending through a lamina portion of the vertebra when the handle axis is oriented substantially perpendicular to a central  
30           axis of the vertebra.

          40. The assembly of claim 36 wherein the insertion path guide surface comprises a tube.

          41. The assembly of claim 36 wherein the insertion path guide surface is adapted and configured to accommodate a drill bit.

35

1 OF 15




Fig. 1

2 OF 15




Fig. 2




Fig. 3

3 OF 15




Fig. 4

4 OF 15




Fig. 5



5 OF 15




Fig. 6

6 OF 15




Fig. 7A

Fig. 7B




Fig. 7C




Fig. 7D




Fig. 7E





Fig. 7F




Fig. 8A




Fig. 8B




Fig. 8C




Fig. 8D

10 OF 15




Fig. 9




Fig. 10A




Fig. 10B




Fig. 10C




Fig. 10D

12 OF 15




Fig. 11



13 OF 15




Fig. 12

14 OF 15




Fig. 13

15 OF 15




Fig. 14

# INTERNATIONAL SEARCH REPORT

PCT/US2004/011335

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A61F2/46 A61B17/17

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 01/30248 A (REILEY M.A.) 3 May 2001 (2001-05-03) page 16, line 19 - page 17, line 23 page 18, line 3 - line 16 page 18, line 28 - page 19, line 7 page 24, line 6 - line 14 page 25, line 11 - line 19 page 26, line 22 - line 26 figures 9,11-13,21	1,15,20, 27
A	US 5 571 191 A (FITZ W.R.) 5 November 1996 (1996-11-05) figures 1,3,4	1,15,20, 27
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

11 October 2004

Date of mailing of the international search report

20/10/2004

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Nice, P

# INTERNATIONAL SEARCH REPORT

PCT/US2004/011335

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 6 132 464 A (MARTIN J.-R.)  17 October 2000 (2000-10-17)  column 2, line 53 - line 55  column 3, line 31 - line 52  column 3, line 66 - column 4, line 4  column 5, line 4 - line 14  column 7, line 41 - line 48  figures 1,2</p>	<p>1,15,20,  27</p>

**FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210**

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-14

Tool for adjusting spacing between facet joint prosthesis bearing elements  
---

2. claims: 15-41

Tool for guiding insertion path of a facet joint prosthesis fixation element  
---

# INTERNATIONAL SEARCH REPORT

PCT/US2004/011335

## Box II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

# INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/US2004/011335

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0130248	A	03-05-2001	AU 776041 B2	26-08-2004
			AU 1229501 A	08-05-2001
			CA 2386504 A1	03-05-2001
			EP 1223872 A1	24-07-2002
			WO 0130248 A1	03-05-2001
			US 2002123806 A1	05-09-2002
			US 2003028250 A1	06-02-2003
			US 2004006391 A1	08-01-2004
			US 2004049281 A1	11-03-2004
			US 2004049272 A1	11-03-2004
			US 2004111154 A1	10-06-2004
			US 2004049273 A1	11-03-2004
			US 2004049274 A1	11-03-2004
			US 2004049275 A1	11-03-2004
			US 2004049276 A1	11-03-2004
			US 2004049277 A1	11-03-2004
			US 2004049278 A1	11-03-2004
			US 6610091 B1	26-08-2003
US 5571191	A	05-11-1996	US RE36758 E	27-06-2000
US 6132464	A	17-10-2000	FR 2721501 A1	29-12-1995
			AT 173601 T	15-12-1998
			AU 2797095 A	19-01-1996
			CA 2193697 A1	04-01-1996
			DE 69506254 D1	07-01-1999
			EP 0767637 A1	16-04-1997
			WO 9600049 A1	04-01-1996



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKÉWED/SLANTED IMAGES**

☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☒ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)